

重量表 · 鋼管

構造用鋼管 · STK400	
規 格	重量 · kg/m
27.2*1.9	1.19
27.2*2.3	1.41
34.0*2.3	1.8
42.7*2.3	2.29
42.7*2.4	2.39
48.6*2.3	2.63
48.6*2.4	2.73
60.5*2.3	3.3
60.5*2.8	3.98
60.5*3.2	4.52
76.3*3.2	5.77
76.3*4.2	7.47
89.1*2.8	5.96
89.1*3.2	6.78
89.1*4.2	8.79
101.6*3.2	7.76
101.6*4.2	10.1
114.3*3.5	9.56
114.3*4.5	12.2
139.8*3.5	11.8
139.8*4.5	15
165.2*4.5	17.8
165.2*5.0	19.8
190.7*5.3	24.2
216.3*4.5	23.5
216.3*5.8	30.1
216.3*8.2	42.1

構造用鋼管 · STK400	
規 格	重量 · kg/m
267.4*6.0	38.7
267.4*6.6	42.4
267.4*9.3	59.2
318.5*6.9	53
318.5*10.3	78.3
355.6*7.9	67.7
355.6*9.5	81.1
355.6*11.1	94.3
406.4*7.9	77.6
406.4*9.5	93
406.4*12.7	123
457.2*6.4	71.1
457.2*7.9	87.5
457.2*9.0	99.5
457.2*9.5	105
457.2*12.7	139
457.2*16.0	205
500.0*6.4	77.9
500.0*7.9	95.9
500.0*9.5	115
500.0*12.7	153
500.0*16.0	191
508.0×6.4	79.2
508.0×7.9	97.4
508.0×9.0	111
508.0×12.7	155
508.0×16.0	194

瓦斯管 · SGP	
規 格	重量 · kg/m
6A(10.5*2.0)	0.419
8A(13.8*2.3)	0.652
10A(17.3*2.3)	0.851
15A(21.7*2.8)	1.31
20A(27.2*2.8)	1.68
25A(34.0*3.2)	2.43
32A(42.7*3.5)	3.38
40A(48.6*3.5)	3.89
50A(60.5*3.8)	5.31
65A(76.3*4.2)	7.47
80A(89.1*4.2)	8.79
90A(101.6*4.2)	10.1
100A(114.3*4.5)	12.2
125A(139.8*4.5)	15
150A(165.2*5.0)	19.8
175A(190.7*5.3)	24.2
200A(216.3*5.8)	30.1
225A(241.8*6.2)	36
250A(267.4*6.6)	42.4
300A(318.5*6.9)	53
350A(355.6*7.9)	67.7
400A(406.4*7.9)	77.6
450A(457.2*7.9)	87.5
500A(508.0*7.9)	97.4

SUS304 鋼管 TP Sch5s	
規 格	重量 · kg/m
6A(10.5*1.0)	0.237
8A(13.8*1.2)	0.377
10A(17.3*1.2)	0.481
15A(21.7*1.65)	0.824
20A(27.2*1.65)	1.05
25A(34.0*1.65)	1.33
32A(42.7*1.65)	1.69
40A(48.6*1.65)	1.93
50A(60.5*1.65)	2.42
65A(76.3*2.1)	3.88
80A(89.1*2.1)	4.55
90A(101.6*2.1)	5.2
100A(114.3*2.1)	5.87
125A(139.8*2.8)	9.56
150A(165.2*2.8)	11.3
200A(216.3*2.8)	14.9
250A(267.4*3.4)	22.4
300A(318.5*4.0)	31.3
350A(355.6*4.0)	35
400A(406.4*4.5)	45.1
450A(457.2*4.5)	50.7
500A(508.0*5.0)	62.6
550A(558.8*5.0)	69
600A(609.6*5.5)	82.8

SUS304 鋼管 TP Sch10s	
規 格	重量 · kg/m
6A(10.5*1.2)	0.278
8A(13.8*1.65)	0.499
10A(17.3*1.65)	0.643
15A(21.7*2.1)	1.03
20A(27.2*2.1)	1.31
25A(34.0*2.8)	2.18
32A(42.7*2.8)	2.78
40A(48.6*2.8)	3.19
50A(60.5*2.8)	4.02
65A(76.3*3.0)	5.48
80A(89.1*3.0)	6.43
90A(101.6*3.0)	7.37
100A(114.3*3.0)	8.32
125A(139.8*3.4)	11.6
150A(165.2*3.4)	13.7
200A(216.3*4.0)	21.2
250A(267.4*4.0)	26.2
300A(318.5*4.5)	35.2
350A(355.6*5.0)	43.7
400A(406.4*5.0)	50
450A(457.2*5.0)	56.3
500A(508.0*5.5)	68.8
550A(558.8*5.5)	75.8
600A(609.6*6.5)	97.7

SUS304 鋼管 TP Sch20s	
規 格	重量 · kg/m
6A(10.5*1.5)	0.336
8A(13.8*2.0)	0.588
10A(17.3*2.0)	0.762
15A(21.7*2.5)	1.2
20A(27.2*2.5)	1.54
25A(34.0*3.0)	2.32
32A(42.7*3.0)	2.97
40A(48.6*3.0)	3.41
50A(60.5*3.5)	4.97
65A(76.3*3.5)	6.35
80A(89.1*4.0)	8.48
90A(101.6*4.0)	9.72
100A(114.3*4.0)	11
125A(139.8*5.0)	16.8
150A(165.2*5.0)	20
200A(216.3*6.5)	34
250A(267.4*6.5)	42.2
300A(318.5*6.5)	50.5
350A(355.6*8.0)	69.3
400A(406.4*8.0)	79.4
450A(457.2*8.0)	89.5
500A(508.0*9.5)	118
550A(558.8*9.5)	130
600A(609.6*9.5)	142